REDCOAT GUITAR SERIES

MAN O WAR™

The Eminence Man O War guitar speaker is the work horse of tone. A proven and revered sound, very loud and responsive/articulate in every register. Chunky, solid low end and crisp mids and highs.

12" 120 WATTS 8 OR 16 Ω



SPECIFICATION

MOUNTING INFORMATION


Shipping Weight

MATERIALS OF CONSTRUCTION

Nominal Basket Diameter	12", 305 mm	Enclosure Type		Copper voice coil
Nominal Impedance*	8 or 16 Ω	Closed Back	Acceptable	Polyimide former
Power Rating*	120 W	Open Back	Acceptable	Ferrite magnet
Resonance (Fs)	91 Hz	Driver Volume Displaced	0.071 cu.ft., 2 liters	Non-vented core
Usable Frequency Range	80 Hz – 5 kHz	Overall Diameter	12.03", 305.6 mm	Pressed steel basket
Sensitivity*	101.6 dB	Baffle Hole Diameter	11.07", 281.2 mm	Paper cone
DC Resistance (Re)	6.2 Ω	Depth	5.2", 132.1 mm	Paper cone edge
Qts	0.68	Front Sealing Gasket	Yes	Zurette dust cap
Magnet Weight	38 oz.	Rear Sealing Gasket	Yes	
Gap Height	0.31", 7.9 mm	Mounting Holes Diameter	0.25", 6.4 mm	
Voice Coil Diameter	1.75", 44 mm	Mounting Holes B.C.D.	11.59", 294.4 mm	
		Net Weight	8.1 lbs , 3.67 kg	

9.9 lbs , 4.49 kg

FREQUENCY RESPONSE & IMPEDANCE CURVE*







See footnotes on page 155 for information regarding usable frequency range, nominal impedance, power rating and sensitivity.