

COMPRESSION DRIVERS

D³



N320T-8

SCREW-ON

BOLT-ON

SPECIFICATION

Throat Size	2.0", 50.8 mm
Nominal Impedance*	8 Ω
Minimum Impedance	6.7 ohm @ 3.6 kHz
Power Rating*	100 W (AES)
Resonance	521 Hz
DC Resistance (Re)	4.80 Ω
Usable Frequency Range	800 Hz - 20 kHz
Recommended Crossover	800 Hz / 12 dB
Sensitivity*	110.4 dB
Magnet Material	Neodymium
Magnet Weight	11 oz, 0.31 kg
Voice Coil Diameter	3.0", 76 mm
Voice Coil Former	Polyimide
Diaphragm Material	Titanium

MOUNTING INFORMATION

Overall Diameter	5.72", 145.3 mm
Driver Volume Displaced	0.028 cu. ft., 0.81 liters
Depth	3.10", 78.7 mm
Net Weight	5.5 lb, 2.5 kg
Shipping Weight	5.8 lb, 2.6 kg
Mounting Thread	N/A
Mounting Holes Diameter	4X 1/4-20
Mounting Holes B.C.D.	4.00", 101.6 mm

FREQUENCY RESPONSE & IMPEDANCE CURVE*

