



RBT-1000

Order No.: 10.1610

Price upon request

PRODUCTINFOS

Ribbon tweeter for PA and hi-fi, 40 W, 6 Ω

- Magnetostatic speaker with waveguide
- Tweeter system from the L-RAY/1000
- Fine and brilliant reproduction of the high range
- For use from 3,000 Hz (hi-fi) or 4,000 Hz (PA) on via 18 dB filter
- Diecast aluminium horn front attachment, neodymium magnet
- Vertical or horizontal mounting possible due to square front panel

TECHNICAL SPECIFICATIONS

RBT-1000

Impedance (Z)	6 Ω
Frequency range	fx-22,000 Hz
Resonant frequency (fs)	1.6 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	> 2,500 Hz

RBT-1000

Power rating	40 W
Peak music power output	80 W
Sensitivity	96 dB/W/m
Magnet diameter	magnetostatic speaker
Mounting cutout	94 x 94 mm
Mounting depth	34 mm
Hole spacing X-axis	87 mm
Hole spacing Y-axis	87 mm
Dimensions	104 x 104 x 24 mm
Width	104 mm
Height	104 mm
Depth	24 mm
Admiss. ambient temp.	0-40 °C
Weight	237 g
Sales unit	1