



## SPM-200X/4

Order No.: 10.5370

**Price upon request**

### PRODUCTINFOS

**Full range speaker, 30 W, 4  $\Omega$**

- Sheet steel basket
- Paper cone with dual cone
- Wide frequency response
- High efficiency
- For PA and hi-fi applications
- Subwoofer support required for hi-fi applications

### TECHNICAL SPECIFICATIONS

#### SPM-200X/4

Impedance (Z)	4 $\Omega$
Frequency range	f3-15,000 Hz
Resonant frequency (fs)	89 Hz
Power rating	30 W

**SPM-200X/4**

Peak music power output	60 W
Sensitivity	94 dB/W/m
Suspension compl. (Cms)	0.27 mm/N
Moving mass (Mms)	9.9 g
Mech. Q factor (Qms)	2.69
Electr. Q factor (Qes)	1.52
Total Q factor (Qts)	0.97
Equivalent volume (Vas)	14.9 l
DC resistance (Re)	3.7 $\Omega$
Force factor (BxL)	3.9 Tm
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	$\varnothing$ 25 mm
Voice coil former	aluminium
Linear excursion ( $X_{MAX}$ )	$\pm$ 1 mm
Eff. cone area (Sd)	201 cm <sup>2</sup>
Magnet weight	229 g
Magnet diameter	$\varnothing$ 70 mm
Mounting cutout	$\varnothing$ 184 mm
Mounting depth	76 mm
Mounting hole diameter	$\varnothing$ 194 mm
Dimensions	$\varnothing$ 205 mm x 82 mm
Outside diameter	$\varnothing$ 205 mm
Width	$\varnothing$ 205 mm
Depth	82 mm
Admiss. ambient temp.	0-40 °C
Weight	0.734 kg
Sales unit	1
Type of speaker	8"