



SPP-200

Order No.: 10.1080

Price upon request

PRODUCTINFOS

Bass-midrange speaker, 30 W, 8 Ω

For general applications.

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hi-fi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-200

| | |
|-------------------------|-------------|
| Impedance (Z) | 8 Ω |
| Frequency range | f3-3,500 Hz |
| Resonant frequency (fs) | 45 Hz |
| Power rating | 30 W |
| Peak music power output | 60 W |
| Sensitivity | 92 dB/W/m |

SPP-200

| | |
|--------------------------------|------------------------------|
| Suspension compl. (Cms) | 0.75 mm/N |
| Moving mass (Mms) | 16.7 g |
| Mech. Q factor (Qms) | 3.96 |
| Electr. Q factor (Qes) | 1.35 |
| Total Q factor (Qts) | 1.00 |
| Equivalent volume (Vas) | 48 l |
| DC resistance (Re) | 6.5 Ω |
| Force factor (BxL) | 4.8 Tm |
| Voice coil induct. (Le) | 0.6 mH |
| Voice coil diameter | \varnothing 25.5 mm |
| Voice coil former | aluminium |
| Linear excursion (X_{MAX}) | \pm 1 mm |
| Eff. cone area (Sd) | 214 cm ² |
| Magnet weight | 280 g |
| Magnet diameter | \varnothing 80 mm |
| Mounting cutout | \varnothing 184 mm |
| Mounting depth | 81 mm |
| Mounting hole diameter | \varnothing 192 mm |
| Hole spacing X-axis | 135 mm |
| Hole spacing Y-axis | 135 mm |
| Dimensions | \varnothing 205 mm x 90 mm |
| Outside diameter | \varnothing 205 mm |
| Width | \varnothing 205 mm |
| Depth | 90 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 0.96 kg |
| Sales unit | 1 |
| Type of speaker | 8" |