

# C 522 ENG

## STEREO REPORTERS' MICROPHONE



Two condenser cardioid capsules angled at 90° for XY stereo. Cable connector doubles as automatic on/off switch. Rechargeable battery/phantom powering. Battery charging either by commercial charger or from phantom power during operation. Battery operating time: 50 to 150 hrs. Rugged all-metal case. Battery check LED.

The C 522 ENG is a simple and professional tool for making excellent stereo features, interviews, music recordings, etc. Connects to all types of recorders (with balanced or unbalanced inputs). For handheld or stand mounted use.

### STANDARD ACCESSORIES

- SA 41/1 Stand adapter
- H 30 Shock-mount stand adapter
- W 52 Foam windscreen
- MK 52/3 3-m (10-ft.) connecting cord with two 3-pin XLR connectors
- MK 52/3 U 3-m (10-ft.) connecting cord with 3.5-mm stereo jack plug
- Strong carrying case for microphone and accessories

### SPECIFICATIONS

Polar Pattern:	2 x cardioid
Frequency Range:	20 – 20,000 Hz
Sensitivity:	10 mV/Pa
Max. Sensitivity Difference between Channels:	2 dB
Impedance:	200 ohms
Equivalent Noise Level:	32 dB (CCIR 468-2) 20 dB·A (DIN 45412-A)
S/N Ratio:	74 dB
Max. SPL for 0.5% THD:	128 dB
Connector:	5-pin XLR
Size:	52/27 Ø x 215 mm (2/1.1 Ø x 8.5 in.)
Net/Shipping Weight:	300 g/1 kg (11 oz/2.2 lbs.)

