


# 54/7414

## 54LS/74LS14

### HEX SCHMITT TRIGGER INVERTER

#### CONNECTION DIAGRAM PINOUT A



**ORDERING CODE:** See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 \text{ V} \pm 5\%$ , $T_A = 0^\circ \text{C to } +70^\circ \text{C}$	$V_{CC} = +5.0 \text{ V} \pm 10\%$ , $T_A = -55^\circ \text{C to } +125^\circ \text{C}$	
Plastic DIP (P)	A	7414PC, 74LS14PC		9A
Ceramic DIP (D)	A	7414DC, 74LS14DC	5414DM, 54LS14DM	6A
Flatpak (F)	A	7414FC, 74LS14FC	5414FM, 54LS14FM	3I

**INPUT LOADING/FAN-OUT:** See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	0.5/0.25
Outputs	20/10	10/5.0 (2.5)

**DC AND AC CHARACTERISTICS:** See Section 3\*

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max		
$V_{T+}$	Positive-going Threshold Voltage	1.5	2.0	1.5	2.0	V	$V_{CC} = +5.0 \text{ V}$
$V_{T-}$	Negative-going Threshold Voltage	0.6	1.1	0.6	1.1	V	$V_{CC} = +5.0 \text{ V}$
$V_{T+} - V_{T-}$	Hysteresis Voltage	0.4		0.4		V	$V_{CC} = +5.0 \text{ V}$
$I_{T+}$	Input Current at Positive- going Threshold	-0.43**		-0.14**		mA	$V_{CC} = +5.0 \text{ V}$ , $V_{IN} = V_{T+}$
$I_{T-}$	Input Current at Negative- going Threshold	-0.56**		-0.18**		mA	$V_{CC} = +5.0 \text{ V}$ , $V_{IN} = V_{T-}$
$I_{IL}$	Input LOW Current	-1.2		-0.4		mA	$V_{CC} = \text{Max}$ , $V_{IN} = 0.4 \text{ V}$
$I_{OS}$	Output Short Circuit Current	-18	-55	-20	-100	mA	$V_{CC} = \text{Max}$ , $V_{OUT} = 0 \text{ V}$
$I_{CCH}$	Power Supply Current	36		16		mA	$V_{CC} = \text{Max}$
$I_{CCL}$		60		21			
$t_{PLH}$ $t_{PHL}$	Propagation Delay	22		22		ns	Figs. 3-1, 3-15

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ \text{C}$  and  $V_{CC} = +5.0 \text{ V}$ . \*\*Typical Value