

SANYO

No.2682

**LA7058**

Monolithic Linear IC
Video / Audio Signal Processor for
UHF Band RF Modulator Use

The LA7058, being a video/audio signal processor IC for UHF band RF modulator use, is suited for RF modulators that require no TSG (test signal generator).

The LA7058 contains a video clamp circuit, a white clip circuit, and an audio FM modulator. The characteristics of the LA7058 are highly stable to supply voltage variations because the LA7058 has an internal voltage regulator.

Functions

- Audio FM modulator
- White clip
- Sync pulse peak clamp
- Voltage regulator

Features

- Capable of being operated from low supply voltage ($V_{CC} = 5V$)
- Highly stable to supply voltage variations because of on-chip voltage regulator
- Excellent frequency characteristic of white clip
- Large amplitude of audio carrier and less high-frequency spurious radiation
- Low current dissipation (30% less compared with our similar ICs)
- Minimum number of external parts required
- Low audio distortion

Maximum Ratings at $T_a = 25^\circ C$

			unit
Maximum Supply Voltage	$V_{CC \text{ max}}$	9.0	V
Allowable Power Dissipation	$P_d \text{ max}$ $T_a \leq 70^\circ C$	250	mW
Operating Temperature	T_{opg} $V_{CC} = 5V$	-20 to +80	$^\circ C$
Storage Temperature	T_{stg}	-40 to +150	$^\circ C$

Operating Conditions at $T_a = 25^\circ C$


			unit
Recommended Supply Voltage	V_{CC}	5.0	V
Operating Voltage Range	$V_{CC \text{ op}}$	4.25 to 7.00	V

Operating Characteristics at $T_a = 25^\circ C, V_{CC} = 5.0V$

			min	typ	max	unit
Current Dissipation	I_{CC} SW1,2:A		7	10	13	mA
Video Clamp Voltage	V_{CL} SW1→A, SW2→B		1.35	1.60	1.85	V
White Clip Level	V_{WC} Output voltage at SW1:C is taken as V_1 . $V_{WC} = V_1 - V_{CL}$		1.10	1.14	1.18	Vp-p
Video Output Amplitude	V_{VO} SW1,2:A, 1Vp-p stair step signal is input.		0.95	0.995	1.05	Vp-p

Continued on next page.

Case Outline 3017B-S9IC (unit:mm)



The application circuit diagrams and circuit constants herein are included as an example and provide no guarantee for designing equipment to be mass produced. The information herein is believed to be accurate and reliable. However, no responsibility is assumed by SANYO for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

SANYO: SEP9

Specifications and information herein are subject to change without notice.

SANYO Electric Co., Ltd. Semiconductor Overseas Marketing Div.
Natsume Bldg., 18-6, 2-chome, Yushima, Bunkyo-ku, TOKYO 113 JAPAN


D267K1, TS No.2682-1/2

LA7058

Continued from preceding page.

		min	typ	max	unit
Audio Carrier Amplitude	V_{AO}	1.05	1.30	1.55	Vp-p
Audio Modulation	A	73	81	89	%
	B	81	90	99	%
	C	90	100	110	%
	D	99	110	121	%
	E	109	121	133	%
Audio Distortion	THD	1kHz, 4.5Vp-p signal is input. ±50kHz is taken as 100%.		0.2	1.5

Test Circuit



Equivalent Circuit Block Diagram

