



- DIMENSIONS R AND U ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY. 7.
- PLASTIC BODY. DIMENSION H DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION. THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE GREATER THAN 0.037 (0.940). THE DAMBAR INTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE SMALLER THAN 0.025 (0.635).

DIM	MIN	MAX	MIN	MAX
Α	0.385	0.395	9.78	10.03
в	0.385	0.395	9.78	10.03
С	0.165	0.180	4.20	4.57
E	0.090	0.110	2.29	2.79
F	0.013	0.021	0.33	0.53
G	0.050 BSC		1.27 BSC	
н	0.026	0.032	0.66	0.81
J	0.020		0.51	
к	0.025		0.64	
R	0.350	0.356	8.89	9.04
U	0.350	0.356	8.89	9.04
v	0.042	0.048	1.07	1.21
w	0.042	0.048	1.07	1.21
х	0.042	0.056	1.07	1.42
Y		0.020		0.50
Z	2 °	10 °	2 °	10 °
G1	0.310	0.330	7.88	8.38
K1	0.040		1.02	

	XXXXXXXXX XXXXXXXXG AWLYYWW
XXXXX	= Specific Device Code
Ą	= Assembly Location
WL	= Wafer Lot
ΥY	= Year
WW	= Work Week
G	= Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ", may or may not be present.

DOCUMENT NUMBER:	98ASB42594B	Electronic versions are uncontrolle accessed directly from the Document versions are uncontrolled except	ed except when t Repository. Printed when stamped
STATUS:	ON SEMICONDUCTOR STANDARD		
NEW STANDARD:		" CONTROLLED COPY" in red.	
DESCRIPTION:	20 LEAD PLLC		PAGE 1 OF 2



DOCUMENT NUMBER: 98ASB42594B

PAGE 2 OF 2

ISSUE	REVISION	DATE
E	UPDATED MARKING DIAGRAM. REQ. BY S. FARRETTA	15 FEB 2005
F	UPDATED MAX VALUES FOR DIMENSION F TO 0.021 IN AND 0.53 MM. COR- RECTED GENERIC MARKING INFORMATION. REQ. BY L. JAMES.	25 JUL 2008

ON Semiconductor and with a registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other application in which the failure of the SCILLC product create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use using SCILLC as neglicate to all applicable copyright laws and is not for resale in any manner.