

DATE 08 NOV 2017









NOTES

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
- 2. CONTROLLING DIMENSION: MILLIMETERS
- 3. DIMENSIONS 6 APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
- 4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM 8 THE CENTER OF DIMENSION B, X DIRECTION, AND FROM DATUM A, Y DIRECTION, POSITIONAL TILLERANCE, AS NOTED IN DRAVING, APPLIES TO EACH TERMINAL IN BOTH DI
- 5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE WITH THE PACKAGE DRIENTATION FEATURE.

MILLIMETERS		
MIN.	MAX.	
11.80	12.20	
4.50	4.90	
16.50	16.90	
16.70	17.70	
12.80	13.20	
0.95	1.05	
92.80	93.20	
104.60	104.90	
81.80	82.20	
106.90	107.50	
46.75	47.25	
44.30	44.50	
38.80	39.20	
5.40	5.60	
10.60	10.80	
2.20	2.40	
	MIN. 11.80 4.50 16.50 16.70 12.80 0.95 92.80 104.60 81.80 106.90 46.75 44.30 38.80 5.40 10.60	






	PIN POSITION		ll .	PIN POSITION	
PIN	х	Y	PIN	х	Y
1	35.00	-15.00	29	-32.50	-15.00
2	35.00	-18.00	30	-32.50	-18.00
3	32.50	-18.00	31	-35.00	-15.00
4	30.00	-18.00	32	-35.00	-18.00
5	27.50	-18.00	33	-29.25	1.45
6	25.00	-18.00	34	-29.25	4.45
7	17.75	-15.00	35	-22.90	4.70
8	17.75	-18.00	36	-15.75	4.85
9	15.25	-15.00	37	-17.15	1.85
10	15.25	-18.00	38	-33.00	18.00
11	8.00	-15.00	39	-30.50	18.00
12	8.00	-18.00	40	-28.00	18.00
13	5.50	-15.00	41	-25.50	18.00
14	5.50	-18.00	42	-23.00	18.00
15	3.00	-15.00	43	-20.50	18.00
16	3.00	-18.00	44	3.00	18.00
17	-3.00	-15.00	45	5.50	18.00
18	-3.00	-18.00	46	8.00	18.00
19	-5.50	-15.00	47	10.50	18.00
20	-5.50	-18.00	48	13.00	18.00
21	-8.00	-15.00	49	15.50	18.00
22	-8.00	-18.00	50	14.90	14.00
23	-15.25	-18.00	51	17.90	14.00
24	-17.75	-18.00	52	17.00	0.10
25	-20.25	-18.00	53	29.20	18.60
26	-22.75	-18.00	54	35.60	18.55
27	-30.00	-15.00	55	35.00	0.90
28	-30.00	-18.00	56	33.55	-2.10

ה		DTN DE	ISITION	_	DTN DE	ISITION
4	J		A 121.170M			A 1211IIM
4	PIN	X		PIN	X	
4	1	35.00	15.00	29	-32.50	15.00
4	2	35.00	18.00	30	-32.50	18.00
4	3	32.50	18.00	31	-35.00	15.00
	4	30.00	18.00	32	-35.00	18.00
┙	5	27.50	18.00	33	-29.25	-1.45
┙	6	25.00	18.00	34	-29.25	-4.45
	7	17.75	15.00	35	-22.90	-4.70
	8	17.75	18.00	36	-15.75	-4.85
	9	15.25	15.00	37	-17.15	-1.85
	10	15.25	18.00	38	-33.00	-18.00
7	11	8.00	15.00	39	-30.50	-18.00
╗	12	8.00	18.00	40	-28.00	-18.00
7	13	5.50	15.00	41	-25.50	-18.00
7	14	5.50	18.00	42	-23.00	-18.00
7	15	3.00	15.00	43	-20.50	-18.00
7	16	3.00	18.00	44	3.00	-18.00
7	17	-3.00	15.00	45	5.50	-18.00
1	18	-3.00	18.00	46	8.00	-18.00
1	19	-5,50	15.00	47	10.50	-18.00
7	20	-5.50	18.00	48	13.00	-18.00
7	21	-8.00	15.00	49	15.50	-18.00
7	22	-8.00	18.00	50	14.90	-14.00
1	23	-15.25	18.00	51	17.90	-14.00
╗	24	-17.75	18.00	52	17.00	-0.10
1	25	-20.25	18.00	53	29.20	-18.60
1	26	-22.75	18.00	54	35.60	-18.55
_	27	-30.00	15.00	55	35.00	-0.90
Η	28	-30.00	18.00	56	33.55	2.10
Ⅎ		00.00	20,00		00.00	2.10

MOUNTING HOLE POSITION

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code

G = Pb-Free Package

AT = Assembly & Test Site Code

YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb–Free indicator, "G" or microdot "■", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON63482G	Electronic versions are uncontrolle	'
STATUS:	ON SEMICONDUCTOR STANDARD	accessed directly from the Document versions are uncontrolled except	
NEW STANDARD:		"CONTROLLED COPY" in red.	
DESCRIPTION:	PIM56 93X47 (SOLDER PIN)		PAGE 1 OF 2



DOCUMENT	NUMBER:
98AON63482	:G

PAGE 2 OF 2

ISSUE	REVISION	DATE
0	RELEASED FOR PRODUCTION. REQ. BY A. LAI.	24 MAY 2017
Α	UPDATED MARKING DIAGRAM IMAGE. REQ. BY A. LAI.	01 JUN 2017
В	UPDATED MARKING DIAGRAM CODE INFORMATION. REQ. BY A. LAI.	08 NOV 2017

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.